



Saves Your Energy

PRODUKTKORT

21.10.2019


1/4

AL375LED20

Namn: **Tak-/väggarmatur**
ALUNO LED 17W/840
Typ: AL375LED20
GTIN: 6410041032238
E-nummer: 7500378

Beskrivning: Aluno är en universalarmatur för torra- och våtautrymmen såväl inomhus som utomhus. Armaturen är lämplig för bland annat trapphus, korridorer, förråd och garage. Den transparenta stommen underlättar installationsarbetet och ger ett elegant uppåtriktat ljus. Aluno finns även med inbyggd högfrekvensrörelsesensor (radar).

Förpackning: 6/1/42
Enhet: st



Tekniska uppgifter

Elektriska värden

Effektfaktor (cos f) 0.9
Spänning 230 V

Betyg

Kapslingsklass IP54
Effekt 17 W
Skyddsklass II
ETIM 7 EC002892

Mekanisk

Slagtålighet -

Dimensioner

Längd 375 mm
Höjd 122 mm
Bredd 375 mm
Vikt 1.4 kg

Temperaturer

Drifttemperatur -20 ... 30 °C

Teknisk information

Styrning -
Lampsockel LED-mod
Ljuskällor antal och effekt (W) 1x17
Ljuskälla (ILCOS) DS
Ljuskälla LED

Ensto Finland Oy

Ensio Miettisen katu 2
PL 77
06101 Porvoo

Puh. 0204 76 21
Fax. 0204 76 2750

www.ensto.fi



AL375LED20

Material

Optik	Opal kupa
Installation	Yt/infälld
Håltagningsmått diameter (mm)	355
Inbyggnads djup	40 mm
Överkoppling	Överkopplingsbar
Anslutning	3x2,5
Anslutning	Snabbkopplings plint
Färg temperatur	4000 K
CRI	Ra>80
LED- modul ljusflöde	1900 lm
LED- armatur ljusflöde	1520 lm
LED- modul livslängd (L70)	35000 h
Anslutnings effekt	17 W
LED- modulen utbytbar	Ja
LED-armaturens effektivitet	89 lm/W
Quantity of luminaires for MCB C16	120
McAdam rate, SDCM	3
ETIM	
Suitable for wall mounting	x
Suitable for suspended mounting	
Suitable for ceiling mounting	x
Suitable for built-in mounting	x
Suitable for surface mounting	x
Lamp type	LED exchangeable
With lamp	x
Lamp holder	None
Suitable for number of lamps	1
Lamp power	17 W
Lamp power at multiwatt	Not applicable
Type of control gear	LED operating device current-controlled
Control gear included	x
Type of dimming	Not dimmable
Circuit	Parallel-compensated
Suitable for emergency lighting	
Emergency unit integrated	
Nominal voltage	230 V
Colour temperature	4000 K
Material housing	Plastic
Type of surface	Matt
Colour housing	White



AL375LED20

Suitable for light line configuration

Material cover	Plastic, opal
Fit for monitor workplace	
Type of grid	None
Reflector	None
Light sharing	Symmetric
Radiation angle	Open beam
Light outlet	Direct
Length	375 mm
Width	375 mm
Height/depth	122 mm
Built-in height/depth	40 mm
Built-in diameter	355 mm
With movement sensor	
With light sensor	
Protection class	II
Degree of protection (IP)	IP54
Fire resistance "D"	
Build in insulated ceiling, fire-resistance "F with roof"	x
Ambient temperature	-20 ... 30 °C
Filament test according to IEC 60695-2-10	None
System power	17 W
With air slots	
Voltage type	AC
Effective luminous flux	1520 lm
Colour of light	White
Colour rendering index CRI	80-89

